



# Statue of Liberty



Oil Pattern Distance	47	Reverse Brush Drop	40	Oil Per Board	Multi ul
Forward Oil Total	15.64 mL	Reverse Oil Total	9.09 mL	Volume Oil Total	24.73 mL
Tank Configuration	A Only	Tank A Conditioner	FIRE	Tank B Conditioner	TERRAIN

	START	STOP	LOADS	MICS	SPEED	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	2R	7	40	14	A	259	0.0	11.9	11.9	10360
2	13L	13R	5	40	14	A	75	11.9	21.8	9.9	3000
3	14L	14R	2	40	18	A	26	21.8	26.9	5.1	1040
4	15L	15R	2	40	18	A	22	26.9	32.0	5.1	880
5	16L	16R	1	40	18	A	9	32.0	34.5	2.5	360
6	2L	2R	0	40	22	A	0	34.5	40.0	5.5	0
7	2L	2R	0	40	30	A	0	40.0	47.0	7.0	0

	START	STOP	LOADS	MICS	SPEED	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	45	30	A	0	47.0	34.0	-13.0	0
2	14L	14R	2	45	22	A	26	34.0	27.8	-6.2	1170
3	13L	13R	2	45	22	A	30	27.8	21.6	-6.2	1350
4	12L	12R	2	45	18	A	34	21.6	16.5	-5.1	1530
5	11L	11R	2	45	18	A	38	16.5	11.4	-5.1	1710
6	2L	2R	2	45	14	A	74	11.4	7.5	-3.9	3330
7	2L	2R	0	45	14	A	0	7.5	0.0	-7.5	0

Cleaner Ratio Main Mix NA Forward  
Cleaner Ratio Back End Mix NA Reverse  
Cleaner Ratio Back End Distance NA Combined  
Buffer RPM: 4 = 700 | 3 = 500 | 2 = 200 | 1 = 100



Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside:Middle	Middle:Middle	Inside:Middle	Middle: Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	3.05	2.67	1.09	1.09	2.67	3.05

